# NEW RENAULT TRAFIC

November 2021

TRAFIC

# the van designed around you

New Renault Trafic has been redesigned to bring maximum efficiency and personalisation to your journey. With the choice from 2 lengths, 2 roof heights and panel van or crew van versions, the New Trafic range allows for customisation to find the right van for your day-to-day needs. The redesign of New Trafic has optimised storage space and comfort throughout the cabin, enhancing the mobile office and connectivity features, making every journey with New Trafic more enjoyable and efficient. 10 new advanced driver assistance systems up to 4.15m load length



up to 8.9m<sup>3</sup> up to 1166kg up to 2.5t 84 litres of load volume payload towing capacity





## elegant functionality on the road



Dynamic and elegant, the exterior design of the New Renault Trafic is above all functional. The new C-shaped LED headlights and 30% larger electric-folding door mirrors bring a stylish look to the front of New Trafic, while also providing greater visibility. The ergonomic load area allows you to maximise storage and makes it more convenient than ever to transfer cargo. Emphasising the elegance of New Trafic, the 17" alloy wheels make a statement on the road and reflect the attention brought to even the smallest of details.



2

- up to 4.15m of load length thanks to the load-through bulkhead located underneath the passenger seat
   up to 8.9m<sup>3</sup> of load volume
   the load area includes up to 18 anchorage points and 2 LED lights

## optimised load area



With its class-leading load length of 4.15m\* using the load-through bulkhead under the passenger seat, and its capacity of towing up to 2.5 tonnes, nothing can stop the New Renault Trafic. The ergonomically designed load area offers of up to 8.9m3 of volume, along with two LED lights as well as the 18 anchorage points\* to maximise convenience.

\*in L2 version.







- 1. 84 litres of cabin storage including 3 litre glovebox
- 2. wireless smartphone charger
- smartphone integration via AndroidAuto™ or Apple CarPlay™
- 4. mobile office: middle passenger seat folds down to present laptop and clipboard storage

# premium and spacious cabin

The completely redesigned interior on New Trafic brings some of the best features of the Renault Car range to the cabin, delivering a highly premium feel. A brand-new dashboard with chrome inserts and the 4.2" colour display on the instrument panel bring a true feel of quality to New Trafic, along with the 84 litres of convenient storage solutions. Enjoy your journey from start to finish with the new 8" EASY LINK multimedia system and stay connected through the smartphone integration brought by Android Auto or Apple CarPlay, all while charging your device on the new wireless smartphone charger.


#### \*depending on versions.

Android Auto™ is a trademark of Google Inc. Apple CarPlay™ is a trademark of Apple Inc. Dashboard compartment covers are not available on right-hand drive vehicles.









# driving made simple

Drive with complete peace of mind, New Trafic will make your journeys safer. A range of advanced driver assistance systems<sup>(1)</sup> and safety devices allow you to travel with confidence.


#### The 360° parking sensors


Front, rear and side sensors warn you of objects using an audible and visual signal. You no longer need to worry about damaging your bodywork (Optional).


#### **Blind Spot Warning**

This system warns the driver of vehicles in their blind spot and helps avoid collisions when manoeuvring. The driver is alerted by an LED light being activated in the corresponding door mirror (Optional).

(1) It is your responsibility to stay alert, drive safely and be in control of the vehicle at all times. Driver assist features have speed and other limitations and should not be relied on. For more information, please refer to the owner's manual or contact your local dealer.







## an ever safer road

### Active Emergency Braking System

This system is able to detect both moving and stationary vehicles. The driver is warned via a visual and audible alert, if the driver doesn't brake or doesn't brake hard enough the system supports with braking (Standard from Sport).

#### Adaptive Cruise Control

This allows you to maintain a safe distance from the vehicle in front. The system applies the brakes when this distance is too short and then accelerates once the road is clear again (Optional).

#### Lane Departure Warning

This system alerts the driver if they cross the central reservation line involuntarily (Standard from Sport+).

## colours







Glacier White(1)







Magma Red<sup>(1) (3)</sup>



Highland Grey<sup>(2)</sup>



Slate Grey<sup>(2)</sup>



Jet Black<sup>(2)</sup>




Carmin Red<sup>(2)</sup>

## upholstery



'Kompo' upholstery



'Java' upholstery

## wheels



16" 'Siras' wheel trim





17" 'Avens' alloy wheels 17" 'Avens' diamond cut alloy wheels

## tyres

| Type of tyres<br>Tyre/wheel size |  | Summer                                 |                                      |  |  |
|----------------------------------|--|--|--------------------------------------|--|--|
|                                  | 215/65 R16                             | 205/65 R16                             | 205/65 R16                           | 215/60 R17                             | 215/65 R16                             |
| Make                             | Goodyear EfficientGrip Cargo           | Goodyear EfficientGrip Cargo           | Bridgestone Duravis R660             | Goodyear EfficientGrip Cargo           | Continental VanContact 4Season         |
| Fuel efficiency class            | В                                      | В                                      | В                                    | В                                      | С                                      |
| Wet grip class                   | А                                      | А                                      | А                                    | А                                      | А                                      |
| Exterior noise (dB)              | 70 dBA AT 50 mph<br>63.9 dBA AT 30 mph | 69 dBA AT 50 mph<br>61.9 dBA AT 30 mph | 72 dBA AT 50 mph<br>67 dBA AT 30 mph | 69 dBA AT 50 mph<br>62.7 dBA AT 30 mph | 73 dBA AT 50 mph<br>67.1 dBA AT 30 mph |

## standard features


### **Sport+** (in addition to Sport)



image shown is left-hand drive. dashboard storage is open on right-hand drive.



17" 'Avens' diamond cut alloy wheels



Java



technology

keyless entry

interior · climate control

exterior

metallic paint

## safety and security rear parking camera


- 'Lane Departure Warning'
- 'Trafic Sign Recognition'


• 17" alloy wheels with black inserts

body coloured side mouldings

## dimensions

L1H1 Van











L2H1 Van










| H1 Van dimensions (mm)  | LIHI      | L2H1      |
|---|-----------|-----------|
| Maximum load volume (m³)  | 5,8       | 7,75      |
| Exterior dimensions   |           |           |
| Overall length  | 5080      | 5480      |
| Overall width with/without door mirrors                                 | 1956/2283 | 1956/2283 |
| Overall height  | 1971      | 1967      |
| Wheelbase length  | 3 0 9 8   | 3 4 9 8   |
| Front overhang  | 1014      | 1014      |
| Rear overhang   | 968       | 968       |
| Loading area  |           |           |
| Width x length of the load-through facility                             | 510 x 222 | 510 x 222 |
| Loading length on floor   | 2537      | 2937      |
| Loading length on floor (including load-through facility)               | 2950      | 3350      |
| Loading length on floor (including load-through facility into footwell) | 3750      | 4150      |
| Loading length 400mm from the floor                                     | tbc       | 2937      |
| Loading area 1m from the floor  | tbc       | 2650      |
| Maximum loading area width  | 1662      | 1662      |
| Width between wheel arches  | 1268      | 1268      |
| Maximum loading area height   | 1387      | 1387      |
| Sliding side door(s)  |           |           |
| Sliding side door entry width 600mm from the floor                      | 907       | 907       |
| Sliding side door entry 100mm from the floor                            | 1030      | 1030      |
| Sliding side door entry height  | 1284      | 1284      |


| Dimensions H1 van (mm)          | LIHI | L2H1 |
|---------------------------------|------|------|
| Rear door                       |      |      |
| Entry width 70mm from the floor | 1391 | 1391 |
| Entry height                    | 1320 | 1320 |
| Loading sill                    | 552  | 552  |
| Ground clearance                | 160  | 160  |


| H1 Van weights and loads (kg) | LI              | L1H1            |                 |  |
|-------------------------------|-----------------|-----------------|-----------------|--|
| Version                       | SL28            | SL30            | LL30            |  |
| Gross vehicle weight          | 2800            | 2900-3010       | 3010-3070       |  |
| Kerb weight                   | 1783 - 2066     | 1783 - 2066     | 1819 - 2102     |  |
| Max payload                   | 1017            | 1227            | 1251            |  |
| Max load on front axle        | 1625            | 1625            | 1625            |  |
| Max load on rear axle         | 1650            | 1650            | 1650            |  |
| Max towable weight            |                 |                 |                 |  |
| Braked/unbraked Manual        | 750/2000 - 2500 | 750/2000-2500   | 750/2000-2500   |  |
| Max towable weight            |                 |                 |                 |  |
| Braked/unbraked Auto EDC      | 750/1900        | 750/1690 - 1800 | 750/1630 - 1690 |  |















| H2 Van dimensions (mm)  | L1H2      | L2H2      |  |
|---|-----------|-----------|--|
| Maximum load volume (m³)  | 6,7       | 8,9       |  |
| Exterior dimensions   |           |           |  |
| Overall length  | 5080      | 5480      |  |
| Overall width with/without door mirrors                                 | 1956/2283 | 1956/2283 |  |
| Overall height  | 2 4 9 5   | 2498      |  |
| Wheelbase length  | 3 0 9 8   | 3 4 9 8   |  |
| Front overhang  | 1014      | 1014      |  |
| Rear overhang   | 968       | 968       |  |
| Loading area  |           |           |  |
| Width x length of the load-through facility                             | 510 x 222 | 510 x 222 |  |
| Loading length on floor   | 2 5 3 7   | 2937      |  |
| Loading length on floor (including load-through facility)               | 2950      | 3350      |  |
| Loading length on floor (including load-through facility into footwell) | 3750      | 4150      |  |
| Loading length 400mm from the floor                                     | 2 5 3 7   | 2937      |  |
| Loading area 1m from the floor  | 2 2 5 0   | 2650      |  |
| Maximum loading area width  | 1662      | 1662      |  |
| Width between wheel arches  | 1268      | 1268      |  |
| Maximum loading area height   | 1898      | 1898      |  |
| Sliding side door(s)  |           |           |  |
| Sliding side door entry width 600mm from the floor                      | 907       | 907       |  |
| Sliding side door entry 100mm from the floor                            | 1030      | 1030      |  |
| Sliding side door entry height  | 1284      | 1284      |  |

| Dimensions H2 van (mm)          | L1H2 | L2H2 |  |
|---------------------------------|------|------|--|
| Rear door                       |      |      |  |
| Entry width 70mm from the floor | 1391 | 1391 |  |
| Entry height                    | 1820 | 1820 |  |
| Loading sill                    | 552  | 552  |  |
| Ground clearance                | 160  | 160  |  |

| H2 Van weights and loads (kg)               | L1H2     | L2H2     |
|---|----------|----------|
| Version                                     | SH30     | LH30     |
| Gross vehicle weight                        | tbc      | tbc      |
| Kerb weight                                 | tbc      | tbc      |
| Max payload                                 | tbc      | tbc      |
| Max load on front axle                      | 1625     | 1625     |
| Max load on rear axle                       | 1650     | 1650     |
| Max towable weight (Braked/unbraked Manual) | 750/2500 | 750/2500 |

## technical specifications

|  | Blue dCi 110                                 | Blue dCi 130             | Blue dCi 150          | Blue dCi 150 EDC6                | Blue dCi 170       | Blue dCi 170 EDC6                |
|--|--|--------------------------|-----------------------|----------------------------------|--------------------|----------------------------------|
| Engine capacity/number of cylinders/valves               | 1997/4/16                                    | 1997/4/16                | 1997/4/16             | 1997/4/16                        | 1997/4/16          | 1997/4/16                        |
| Max. power kW ECC (hp) at rpm                            | 81 (110) at 3 500                            | 96 (130) at 3 500        | 110 (150) at 3 500    | 110 (150) at 3 500               | 125 (170) at 3 500 | 125 (170 ) at 3 500              |
| Max. torque Nm ECC at rpm                                | 300 at 1500                                  | 320 at 1500              | 350 at 1500           | 350 at 1500                      | 380 at 1500        | 380 at 1500                      |
| Type of injection  |  |                          | common rail direc     | t injection (2500 bar)           |                    |                                  |
| Fuel and tank volume (L)                                 |  |                          | dies                  | sel - 80                         |                    |                                  |
| Adblue® fuel tank volume (1) (L)                         |  |                          | :                     | 24.7                             |                    |                                  |
| Emission control standard                                |  |                          | Euro                  | 6 d-full                         |                    |                                  |
| Gearbox type   | manual gearbox                               | manual gearbox           | manual gearbox        | automatic gearbox<br>dual clutch | manual gearbox     | automatic gearbox<br>dual clutch |
| Number of gears  |  |                          |                       | 6                                |                    |                                  |
| Maintenance interval                                     |  |                          | up to 24,000          | miles/2 years <sup>(2)</sup>     |                    |                                  |
| Performance  |  |                          |                       |                                  |                    |                                  |
| Top speed (mph)  | 103  | 109                      | 109                   | 110                              | tbc                | 115                              |
| 0-62 mph (s)   | 16.8   | 14.3                     | tbc                   | 11.6                             | tbc                | 10.6                             |
| Fuel consumption and emissions <sup>(3)</sup>            |  |                          |                       |                                  |                    |                                  |
| Certification cycle                                      |  |                          | W                     | LTP <sup>(4)</sup>               |                    |                                  |
| Combined fuel consumption (mpg)                          | 39.8-40.9                                    | tbc                      | tbc                   | tbc                              | tbc                | tbc                              |
| CO <sup>2</sup> emissions (g/km)                         | 182-186                                      | tbc                      | tbc                   | tbc                              | tbc                | tbc                              |
| Steering   |  |                          |                       |                                  |                    |                                  |
| Turning circle between kerbs (m)                         | short wheelbase: 12.4 - Long wheelbase: 13.8 |                          |                       |                                  |                    |                                  |
| Turning circle between walls (m)                         |  |                          | short wheelbase: 12.8 | 8 - Long wheelbase: 14.3         |                    |                                  |
| Braking  |  |                          |                       |                                  |                    |                                  |
| ABS with EBD (Electronic brake force distribution)       | standard                                     |                          |                       |                                  |                    |                                  |
| Front: ventilated disks - Rear: solid disks Ø/width (mm) | 296/28 - 280/12                              |                          |                       |                                  |                    |                                  |
| Tyres  |  |                          |                       |                                  |                    |                                  |
| Tyre/wheel size  |  | 205/65 R16<br>15/60 R17" |                       | standard : 2<br>option : 218     |                    |                                  |

- = not available.. (1) homologation in progress. The actual consumption of fuel and AdBlue depends on the conditions of use of the vehicle, the equipment, the driving style of the driver and the load. (2) an engine consumes oil for lubricating and cooling its moving parts. it is normal to top up the oil once or several times between two changes. (3) WLTP figures shown are for comparability purposes. Actual real-world driving results may vary depending on factors such as weather conditions, driving styles, vehicle load or any accessories fitted after registration. Depending on options fitted WLTP figures may differ. Please consult with local dealer or refer to www.business.renault.co.uk/configurator for more information. (4) WLTP (Worldwide harmonized Light vehicles Test procedures); this new protocol makes it possible to obtain results move closer to those observed during the daily trips carried out than the NEDC protocol.

## Renault PRO+, the specialist brand



You're the expert in your field and at Renault PRO+ we're here to guide you through ours. We're passionate about delivering products and services to move your business forward. So when you choose to partner with Renault PRO+ you can expect:

#### Specialist network

Renault PRO+ Centres have a dedicated commercial vehicle specialist. So whatever you're seeking advice on, there's always someone to help.

#### **Business Commitment**


Come rain or shine, we have a set of commitments in place to help maximise uptime and minimise downtime.

#### The future today - 100% electric

Renault PRO+ has been building, selling and maintaining electric vans since 2011. So when you're looking to make the switch, you know who to speak to.

#### A tailored approach

Your vehicles are as unique as your business. That's why we have a programme of conversions to deliver exactly the product you want. From 'off the shelf' conversions to a more bespoke approach. We'll guide you through.





www.pilakoutasgroup.com.cy

